


B Turning Insert (Negative)

SN



Dimensions (mm)			
Size	d	t	d ₁
12	12.7	4.76	5.16
15	15.875	6.35	6.35
19	19.05	6.35	7.93
25	25.4	7.94~9.52	9.12

Square **90° Negative**

Workpiece	Machining types												
	P	M	K	N	S	H							
Steel	●	●	●	●	●	●	●	●	●	●	●	●	●
Stainless steel	●	●	●	●	●	●	●	●	●	●	●	●	●
Cast iron	●	●	●	●	●	●	●	●	●	●	●	●	●
Non-ferrous metal	●	●	●	●	●	●	●	●	●	●	●	●	●
Heat resistant alloy, Titanium alloy	●	●	●	●	●	●	●	●	●	●	●	●	●
Hardened steel	●	●	●	●	●	●	●	●	●	●	●	●	●

Inserts	Designation	Cermets		Coated		Coated										Uncoated		Cutting Condition									
		CN1500	CN2000	CN2500	CC1500	CC2500	NC3215	NC3120	NC3225	NC3030	NC5330	NC6310	NC6315	NC9115	NC9125	NC9135	PC5300	PC5400	PC8105	PC8110	PC8115	PC9030	H01	H05	f _n (mm/rev)	a _p (mm)	
Roughing 	SNMG 120404-RM												●	●	●	●					●				0.10~0.50	2.00~6.00	
	120408-RM												●	●	●	●					●	●	●			0.15~0.55	2.00~6.00
	120412-RM													●	●	●					●					0.20~0.60	2.00~6.00
	120416-RM																					●				0.25~0.70	2.00~6.00
	150608-RM																									0.20~0.60	0.20~6.00
	150612-RM													●	●	●						●				0.20~0.60	2.00~8.00
	150616-RM																									0.25~0.70	2.00~8.00
	190608-RM														●	●	●					●				0.20~0.60	2.00~10.00
	190612-RM														●	●	●					●				0.20~0.60	2.00~10.00
	190616-RM																									0.27~0.70	2.00~10.00
	190624-RM																									0.30~0.75	3.00~10.00
250924-RM																									0.40~1.20	4.00~14.00	
Roughing 	SNMG 120408-VP4																								0.15~0.35	1.00~4.00	
	120412-VP4																									0.20~0.40	1.00~4.00
	150612-VP4																									0.20~0.45	1.00~5.00
	190608-VP4																									0.20~0.50	1.00~9.00
	190612-VP4																									0.23~0.55	1.00~9.00
	190616-VP4																									0.27~0.60	1.00~9.00
Roughing 	SNMG 120408-VR																									0.25~0.55	1.20~7.00
	120412-VR																									0.30~0.60	1.50~7.00
	120416-VR																									0.35~0.60	2.00~7.00
	190612-VR						●	●																		0.35~0.70	2.00~10.00
	190616-VR						●	●																		0.35~0.75	2.20~10.00
Roughing 	SNMM 120408-GR																									0.20~0.50	1.00~7.00
	120412-GR								●																	0.25~0.65	1.30~7.00
	190612-GR								●																	0.25~0.65	1.30~11.50
	190616-GR																									0.32~0.85	1.80~11.50

Cutting edge geometry **A52~A61**
 Recommended chip breaker **B04~B11**
 Code system **B26~B27**
● : Stock item

Available tool holders					
Designation	Page	Designation	Page	Designation	Page
MSBNR/L	B173	MSRNR/L	B174	PSDNN	B163
MSDNN	B173	MSSNR/L	B175	PSKNR/L	B164, 199
MSKNR/L	B174	PSBNR/L	B163	PSSNR/L	B164

