




Rhombic 55° Positive
Relief Angle: 7°



Dimensions (mm)			
Size	d	t	d ₁
07	6.35	2.38	2.8
11	9.525	3.97	4.4

Workpiece	Machining types														
	P	M	K	N	S	H									
Steel	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Stainless steel	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Cast iron	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Non-ferrous metal															
Heat resistant alloy, Titanium alloy															
Hardened steel															

● Continuous cutting
● General cutting
✦ Interrupted cutting

Inserts	Designation	Cermet		Coated		Coated										Uncoated		Cutting Condition									
		CN1500	CN2000	CN2500	CC1500	CC2500	NC3215	NC3120	NC3225	NC3030	NC5330	NC6310	NC6315	NC9115	NC9125	NC9135	PC5300	PC5400	PC8105	PC8110	PC8115	PC9030	H01	H05	f _n (mm/rev)	a _p (mm)	
Finishing [High precision]	DCET 0702005MFR-KF																●			●					0.01~0.06	0.04~1.30	
	070201MFR-KF																	●			●					0.02~0.08	0.05~1.50
	070202MFR-KF																	●			●					0.03~0.11	0.06~1.70
	11T3005MFR-KF																	●			●					0.02~0.08	0.05~1.50
	11T301MFR-KF																	●			●					0.03~0.11	0.06~1.70
	11T302MFR-KF																	●			●					0.04~0.15	0.08~2.00
	0702005MFL-KF																	●			●					0.01~0.06	0.04~1.30
	070201MFL-KF																	●			●					0.02~0.08	0.05~1.50
	070202MFL-KF																	●			●					0.03~0.11	0.06~1.70
	11T3005MFL-KF																	●			●					0.02~0.08	0.05~1.50
	11T301MFL-KF																	●			●					0.03~0.11	0.06~1.70
	11T302MFL-KF																	●			●					0.04~0.15	0.08~2.00
Medium to finishing [High precision]	DCET 0702005MFR-KM																	●			●				0.01~0.06	0.04~1.30	
	070201MFR-KM																	●			●					0.02~0.08	0.05~1.50
	070202MFR-KM																	●			●					0.03~0.11	0.06~1.70
	11T3005MFR-KM																	●			●					0.02~0.08	0.05~1.50
	11T301MFR-KM																	●			●					0.03~0.11	0.06~1.70
	11T302MFR-KM																	●			●					0.04~0.15	0.08~2.00
	0702005MFL-KM																	●			●					0.01~0.06	0.04~1.30
	070201MFL-KM																	●			●					0.02~0.08	0.05~1.50
	070202MFL-KM																	●			●					0.03~0.11	0.06~1.70
	11T3005MFL-KM																	●			●					0.02~0.08	0.05~1.50
	11T301MFL-KM																	●			●					0.03~0.11	0.06~1.70
	11T302MFL-KM																	●			●					0.04~0.15	0.08~2.00
Finishing 	DCGT 0702003R-KF																									0.01~0.06	0.04~1.30
	070201R-KF																									0.02~0.08	0.05~1.50
	070202R-KF																									0.03~0.11	0.06~1.50
	11T3003R-KF																									0.02~0.08	0.05~1.50
	11T301R-KF																									0.03~0.11	0.06~1.70
	11T302R-KF																						●			0.04~0.15	0.08~2.00
	0702003L-KF																									0.01~0.06	0.04~1.30
	070201L-KF																									0.02~0.08	0.05~1.50
	070202L-KF																									0.03~0.11	0.06~1.50
	11T3003L-KF																									0.02~0.08	0.05~1.50
	11T301L-KF																									0.03~0.11	0.06~1.70
	11T302L-KF																									0.04~0.15	0.08~2.00

➤ Cutting edge geometry A52~A61 ➤ Recommended chip breaker B04~B11 ➤ Code system B26~B27 ● : Stock item

Available tool holders			
Designation	Page	Designation	Page
SDACR/L	B178	SDQCR/L	B206
SDJCR/L	B113, 179	SDUCR/L	B207
SDNCN	B114, 179	SDZCR/L	B208

